

Appl. No. 09/955,692

Amdt. dated December 31, 2003

Reply to Office action of October 9, 2003

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A cleanup device adapted to transport desired material and at least one tool to a desired position comprising:

- (a) the cleanup device including a dolly and a waste container;
- (b) the dolly being adapted to support at least one tool;
- (c) the dolly being movable to or from the desired position;
- (d) the dolly being releasably securable at the desired position; and
- (e) the waste container being removably secured to the dolly;
- (f) the dolly being supported on a set of casters;
- (g) the set of casters supporting the cleanup device;
- (h) the set of casters providing mobility to the cleanup device;
- (i) the dolly including an interior compartment supported on a set of casters;
- (j) the interior compartment being adapted to receive a cleaning material;
- (k) the dolly having a side opening and a top opening;
- (l) the side opening serving to permit removal of the cleaning material therefrom at the desired position;
- (m) the top opening serving to permit addition of the cleaning material to the dolly;
- (n) the dolly having at least one shelf on the at least one side of the dolly may provide a tool support;
- (o) the at least one shelf being adapted to support a tool to be carried to the desired position;
- (p) an indentation adapted to receive the waste container being adjacent to the top opening;
- (q) the top opening being closable by the waste container in the indentation;
- (r) at least one mounted gripping device being on the waste container; and
- (s) the at least one shelf cooperating with the at least one mounted gripping device in order to support a tool on the cleanup device.

Appl. No. 09/955,692

Amdt. dated December 31, 2003

Reply to Office action of October 9, 2003

2. (now cancelled)

3. (once amended) The cleanup device of ~~Claim 2~~ Claim 1 further comprising:

- ~~(a) the dolly having a side opening and a top opening;~~
- ~~(b) the side opening serving to permit removal of the cleaning material therefrom at the desired position;~~
- ~~(c) the top opening serving to permit addition of the cleaning material to the dolly; and~~
- ~~(d) the dolly having a generally polygonal shape.~~

4. (now cancelled)

5. (now cancelled)

6. (once amended) The cleanup device of ~~Claim 4~~ Claim 1 further comprising:

- (a) a skirt being mounted on the drum waste container;
- (b) at least one mounted gripping device being on the skirt; and
- (c) the at least one shelf cooperating with the at least one mounted gripping device in order to support a tool on the cleanup device.

7. (once amended) The cleanup device of ~~Claim 4~~ Claim 1 further comprising:

- (a) a lid being adapted to cover the drum waste container; and
- (b) a fastening device attaching the lid to drum the waste container.

8. (once amended) The cleanup device of ~~Claim 4~~ Claim 1 further comprising:

- (a) a flexible closure being adapted to cover the side opening;
- (b) the flexible closure being secured to an edge of the side opening; and
- (c) the flexible closure serving to contain the cleaning material within the dolly, while providing access thereto.

Please cancel Claims 2, 4, 5, 14 to 16, 19 and 20.

Appl. No. 09/955,692

Amdt. dated December 31, 2003

Reply to Office action of October 9, 2003

9. (once amended) The cleanup device of ~~Claim 4~~ Claim 1 further comprising:

- (a) the set of casters including a pair of lockable casters and a pair of free casters;
- (b) the pair of lockable casters having locked position and an unlocked position; and
- (c) the locked position serving to releasably fix the position of the cleanup device.

10. (once amended) The cleanup device of Claim 9 further comprising:

- (a) the pair of lockable casters being oppositely disposed from the side opening;
- (b) the ~~skirt dolly~~ including at least one fastener; and
- (c) the at least one fastener cooperating with the shelf in order to hold a desired item.

11. (once amended) The cleanup device of Claim 10 further comprising:

- (a) the at least one fastener being at least one selected from a snap assembly, a pinned assembly, a hook and loop assembly, a rivet assembly, a nut and bolt assembly, and glue; and
- (b) a lid strap being adapted to secure the lid to the drum waste container.

12. (once amended) The cleanup device of Claim 10 further comprising:

- (a) the waste container having a disposable bag mounted therein; and
- (b) the cleanup device being adapted to receive at least one tool selected from the group consisting of a broom, a dustpan, a utility bag, and the lid strap.

Appl. No. 09/955,692

Amdt. dated December 31, 2003

Reply to Office action of October 9, 2003

13. (once amended). A cleanup device adapted to transport desired material and at least one tool to a desired position comprising:
- (a) the cleanup device including a dolly and a waste container;
  - (b) the dolly being adapted to support at least one tool;
  - (c) the dolly being movable to or from the desired position;
  - (d) the dolly being releasably securable at the desired position;
  - (e) the waste container being removably secured to the dolly;
  - (f) the dolly being supported on a set of casters;
  - (g) the set of casters supporting the cleanup device;
  - (h) the set of casters providing mobility to the cleanup device;
  - (i) the set of casters including a pair of lockable casters and a pair of free casters;
  - (j) the pair of lockable casters having locked position and an unlocked position; and
  - (k) the locked position serving to releasably fix the position of the cleanup device;
  - (l) the dolly including an interior compartment;
  - (m) the dolly having a side opening and a top opening;
  - (n) the side opening serving to permit removal of the cleaning material therefrom at the desired position;
  - (o) the top opening serving to permit addition of the cleaning material to the dolly;
  - (p) the dolly having a generally polygonal shape;
  - (q) the dolly having at least one shelf on the at least one side of the dolly may provide a tool support;
  - (r) the at least one shelf being adapted to support a tool to be carried to the desired position;
  - (s) an indentation adapted to receive a waste container being adjacent to the top opening;
  - (t) the top opening being closable by the waste container in the indentation;
  - (u) a skirt being mounted on the waste container;
  - (v) at least one mounted gripping device being on the skirt; and
  - (w) the at least one shelf cooperating with the at least one mounted gripping device in order to support a tool on the cleanup device.

Appl. No. 09/955,692  
Amdt. dated December 31, 2003  
Reply to Office action of October 9, 2003

14. (now cancelled)

15. (now cancelled)

16. (now cancelled)

17. (once amended) The cleanup device of ~~Claim 16~~  
Claim 13 further comprising:

- (a) a lid being adapted to cover the drum waste container;
- (b) a fastening device attaching the lid to drum the waste container;
- (c) a flexible closure being adapted to cover the side opening;
- (d) the flexible closure being secured to an edge of the side opening; and
- (e) the flexible closure serving to contain the cleaning material within the dolly, while providing access thereto.

18. (originally presented) The cleanup device of Claim 17 further comprising:

- (a) the pair of lockable casters being oppositely disposed from the side opening;
- (b) the skirt including at least one fastener; and
- (c) the at least one fastener cooperating with the shelf in order to hold a desired item.

19. (now cancelled)

20. (now cancelled)